



Full Fleet Access Trunked Mobile

T2035

20 preset calls

Multiple network capability

MAP27 data capable

Advanced call handling

Conventional channel mode

- **Full Fleet Dialling** - Enables you to simply select other operators in the same fleet. Three digit dialling allows for large fleet access (0-999).
- **MPT1343 Compatible** - The T2035 is fully MPT1327/ MPT1343 compatible and has MPT1352 approval, ensuring correct operation on the respective trunked network.
- **Conventional Channel Operation** - The T2035 can be used in conventional channel mode to access a conventional radio network or when out of range of the trunking system. A CTCSS option can be fitted on conventional channels.
- **MAP27 Data Capable** - When combined with a data interface kit, the T2035 can be used as a building block for data products. Alternatively, the addition of Direct Connect GPS software provides a GPS solution via the data interface kit.
- **Preset Calls** - 20 presets can be programmed with call strings ranging from standard calls (Despatch calls, Group calls, Status calls) to PSTN numbers, PABX numbers and conventional channels.
- **Automatic Number Identification** - The caller's identity number is displayed on the three digit LED display to allow easy identification of your callers.
- **Multiple Network Capability** - Operates on two different trunking networks for greater flexibility. Choice of network is user selectable via the keypad.
- **Call in Absence Indicator** - If you receive a call while you are away from your vehicle, an alert tone will sound to notify you of an unanswered call. You can call back simply by pressing the microphone key.
- **Multifunction Display** - The three digit display allows selection of preset strings or common fleet numbers. The display also shows queue entries, queue length, a callback number or remaining call time.
- **Call Queuing** - Queues incoming calls for greater efficiency and convenience.
- **Rugged Construction** - Solid, die-cast chassis and covers, and SMD technology for durability.
- **Security** - The T2035 can be locked in its cradle.

CONNECTIVITY • RELIABILITY • FLEXIBILITY

TAIT
T2000
MOBILES



TAIT

Radio Communications

T2035

General Specifications

<http://www.taitworld.com/>

CORPORATE HEAD OFFICE
NEW ZEALAND
Tait Electronics Ltd
P O Box 1645, Christchurch
E-mail: mobiles.marketing@tait.co.nz

AUSTRALIA
Tait Electronics (Aust) Pty Ltd
Toll Free: 1-300 304 344
E-mail: australia@taitworld.com

TAIT NORTH AMERICA INC.
Regional Head Office
CANADA
Toll Free: 1-800-890 TAIT (8248)
E-mail: canada@taitworld.com

USA
Toll Free: 1-800-890 TAIT (8248)
E-mail: usa@taitworld.com

LATIN AMERICA
Tait Latin America
E-mail: latinamerica@taitworld.com

NEW ZEALAND
Tait Communications Ltd
E-mail: headoffice@tcl.tait.co.nz

TAIT EUROPE LTD
Regional Head Office
UNITED KINGDOM
Tait Mobile Radio Ltd
E-mail: sales@tait.co.uk

TAIT NORTH ASIA
Regional Head Office
HONG KONG
Tait Mobile Radio (Hong Kong) Ltd
E-mail: hongkong@taitworld.com

BEIJING
Tait Mobile Radio
(Hong Kong) Ltd
E-mail: beijing@taitworld.com

TAIWAN
Tait Mobile Radio
(Taiwan) Ltd
E-mail: taiwan@taitworld.com

TAIT SOUTH EAST ASIA
Regional Head Office
SINGAPORE
Tait Electronics
(Far East) Pte Ltd
E-mail: singapore@taitworld.com

THAILAND
Tait Mobile Radio Ltd
E-mail: thailand@taitworld.com

Number of Channels
1023 trunked channels
4 conventional channels

Channel Spacing
12.5 kHz
20 kHz
25 kHz

Frequency Ranges
66-88 MHz
136-174 MHz
175-225 MHz
220-270 MHz
330-360 MHz
360-400 MHz
400-470 MHz
450-520 MHz
500-530 MHz
800 MHz: 806-870 MHz Tx
 : 851-870 MHz Rx
900 MHz: 896-941 MHz Tx
 : 935-941 MHz Rx

Size (LxWxH)
188 x 158 x 51mm
7.4" x 6.2" x 2"

Typical Performance Figures

Specifications are subject to change without notice and shall not form part of any contract. They are issued for guidance purposes only. For further information, please contact your nearest Tait office or authorised dealer.

Tait is your complete supplier of radio communications equipment, with Mobile, Portable and Infrastructure solutions.

Weight
1.2 kg
2lb 10oz


Standard Features
Conventional Operation, Automatic Number Identification, Emergency Calls, Status Calls (transmit only), Programmable Economy Mode, Transmit Timer.

Options
DTMF ANI Encode, DTMF Microphone, Heavy-duty Microphone, Desktop Microphone, Hands-free Kit, Power Supply, Remote Speaker, 600Ω Line Interface Kit, Data Interface Kit, CTCSS Module.

Supply Voltage
13.8 V nominal
10.8-16.0 V range

Technical Compliance
For details of technical compliance, contact your nearest Tait office or authorised dealer.

Transmitter Power
25W
22.5W 500-530 MHz
15W 800 MHz, 900 MHz



TAIT Electronics Ltd is an ISO 9001 registered supplier. Certificate No.461.



TAIT Authorised Dealer