



2052 NW 93 Avenue ~ Miami, Florida 33172 U.S.A.  
Phone 305-500-9302 ~ Fax 305-500-9402 ~ info@condorD.com

# CDR700 and CDR500 REPEATER HOUSINGS Wall Mount or Desktop

## Repeater Controllers

### Select Repeater Controller

HLN3948	<b>Basic Interface Repeater Controller</b> Provides repeater functionality, remote knock-down/set-up, in/crossband and uni/bi directional capabilities. Need "B" version to work with the CDR700
HLN9119	<b>ZR340 Advanced Interconnect Controller</b> Provides advanced interconnect capabilities including password driven access and disconnect codes, customized toll restrict and toll restrict bypass. Does not use RSS Programming done via DTMF parameters.
HLN8388	<b>ZR310 Community Repeater Controller</b> Subdivides a repeater into separate groups of users so each group does not have to hear the conversation of the other groups. Up to 70 user groups may be established. Uses GM300 RSS, HVN8177.
HLN9447	<b>i20R Onsite Repeater Controller</b> Subdivides a repeater into separate groups of users so each group does not have to hear conversations of other groups. Up to 10 user groups may be established. Uses i20R RSS, HVN9085
HLN3104	<b>"Enhanced" SmarTrunk II™ Repeater Controller Model ST853</b> Provides trunked repeater functionality, individual selective calling, group calling all fleet calling, conventional operation and advanced interconnect capabilities. The controller has a capacity of 4096 subscribers per system, 4500 call records per controller and 320,000 paging codes. Uses SmarTrunk II™ Programming Software, HVN9021.
HKN9028	<b>"Enhanced" SmarTrunk II™ Repeater Controller Cable</b> Required when using HLN3104 with the HKLN4056, HK1009, HKLN4060 and HK1008 housings.
RLN4744	<b>Zetron Model 42 Dispatched only LTR Controller</b> Includes: 901-9309 Model 42, 950-9915 Model 42 version 6 firmware, -M02 Ghost Repeater option.
RLN4746	<b>Zetron Model 49 Dispatch and 2 wire interconnect LTR Controller</b> Includes: 901-9147 Model 49, 950-9404 version 6 firmware, -M02 Ghost Repeater, -M05 FASTNet interface, -M06 SMDR, -M07 Interconnect, 950-9563 Telephone Interconnect, 950-9547 Full Duplex E-E card (2 wire).
RLN4747	<b>Zetron Model 49 Dispatch and 4 wire interconnect LTR Controller</b> Includes: 901-9147 Model 49, 950-9404 version 6 firmware, -M02 Ghost Repeater, -M05 FASTNet interface, -M06 SMDR, -M07 Interconnect, 950-9561 E/M Type I (4 wire).
3080384G13	Zetron Controller Cable
3080384F66	Controller to Controller Cable 3 feet
3080384F67	Controller to Controller Cable 7 feet



2052 NW 93 Avenue ~ Miami, Florida 33172 U.S.A.  
Phone 305-500-9302 ~ Fax 305-500-9402 ~ info@condorD.com

# CDR700 and CDR500 REPEATER HOUSINGS Wall Mount or Desktop

## Optional

### Select (1) Tuned Duplexer and (1) Duplexer Cable

#### Specify Frequency for Factory Tuning. All duplexers have female type "N" connectors

HFD8465	VHF Duplexer 150-160 MHz (requires Internal Duplexer/Antenna Cable Kit - minimum and maximum frequency separation is 4.5 MHz/6 MHz)
TDE7780	UHF Duplexer 450-470 MHz (requires Internal Duplexer/Antenna Cable Kit - minimum and maximum frequency separation is 5 MHz)

## OR

### Select (1) Untuned Duplexer

RFE4000	UHF Duplexer 450-470 MHz (requires Internal Duplexer/Antenna Cable Kit)
---------	---

#### Duplexers below require tuning in field.

HFD8464	VHF Duplexer, 136-144 MHz
HFD8188	VHF Duplexer, 144-155 MHz (minimum & maximum freq.separation is 4.5 MHz/6 MHz)
HFD8457	VHF Duplexer, 150-160 MHz (minimum frequency separation is 4.5 MHz)
HFD8189	VHF Duplexer, 155-162 MHz (minimum & maximum freq.separation is 4.5 MHz/6 MHz)
HFD8190	VHF Duplexer, 162-174 MHz (minimum & maximum freq.separation is 4.5 MHz/6 MHz)
HFE8400	UHF Duplexer, 406-450 MHz (minimum & maximum freq.separation is 5 MHz)
HFE8401	UHF Duplexer, 470-490 MHz (minimum & maximum freq.separation is 3 MHz)
HFE8454	UHF Duplexer, 490-512 MHz

## Only required if using a Duplexer

HKKN4002	CDR500/CDR700 Internal Duplexer/Antenna Cable
HKKN4001	CDR500/CDR700 Internal Duplexer/Antenna Cable - required when using separate transmit and receive antennas or duplexers that do not fit into CDR500/CDR700 housings.

## Optional

### Select an Antenna

RDD4527	VHF 3dB Gain Antenna, 150-158 MHz
RDE4556	UHF 3.8dB Gain Antenna, 450-470 MHz



2052 NW 93 Avenue ~ Miami, Florida 33172 U.S.A.  
 Phone 305-500-9302 ~ Fax 305-500-9402 ~ info@condorD.com

# CDR700 and CDR500 REPEATER HOUSINGS Wall Mount or Desktop

MODEL NUMBER	DESCRIPTION
--------------	-------------

### Mounting Accessories

HLN9169	CDR500 Wall and 19 inch Panel Mount
HKLN4117	GR500 Radio/Duplexer Mounting Bracket Retrofit Kit - This bracket allows the installation of PRO Series mobiles within a GR500 repeater housing.
HKLN4121	CDR700 Filler Plate Kit - Plate fills the controller slot and ensures proper airflow

### General Accessories

HLN9455	CDR700 and GR1225 Battery Revert/Float Maintenance Charger
HPN9033	110V CDR700 AND GR1225 Power Supply
HPN9005	110V CDR500 and GR500 Power Supply
HKPN4000	230V CDR700 Power Supply (no line cord)
HKPN4001	230V CDR500 Power Supply (no line cord)
AARMN4026	Enhanced Keypad Microphone
HMN3000	Desk Microphone (black)
HKKN4000	Power Sense Cable US Plug (CDR700 Only) - in the event of a power loss, this cable will allow the repeater to power up automatically once A/C is restored.
HLN9457_R	Hardware Kit for use with the Expanded Accessory Connector (includes 16 connector)
NTN7373_R	Line Cord with US Plug for use with HKPN4000 and HKPN4001 Power Supply
NTN7374_R	Line Cord with Euro Plug for use with HKPN4000 and HKPN4001 Power Supply
NTN7375_R	Line Cord with UK Plug for use with HKPN4000 and HKPN4001 Power Supply
NTN9246	Line Cord with Argentina Plug for use with HKPN4000 and HKPN4001 Power Supply

**Preselectors: - Specify Frequency for Factory Tuning**  
**The CDR500 allows for internal mounting of a duplexer and a preselector.**  
**The CDR700 allows for the internal installation of either a duplexer or a preselector.**

All preselectors have a female type "N" connectors. A dealer supplied type "N" male to male connector is required for proper operation. The length of the cable depends on your application. Call Motorola Accessory and Aftermarkets Division (AAD) to find a cable for your individual application.

HFD8463	VHF 136-144 MHz Preselector
HFD8461	VHF 144-160 MHz Preselector (Minimum 3dB Nose Bandwidth 2MHz)
HFD8462	VHF 160-174 MHz Preselector (Minimum 3dB Nose Bandwidth 2MHz)
HFE8458	UHF 406-440 MHz Preselector
HFE8459	UHF 440-474 MHz Preselector (Minimum 3dB Nose Bandwidth 3MHz)
HFE8460	UHF 474-512 MHz Preselector

### Lightning Protection Recommendation Accessories

#### Phone/Remote Line Suppressors

RRX4021	Single Line Suppressor
TRN4589	Dual Line Suppressor

#### AC Line Surge Protector

RLN4264	120VAC, 15A 3-Prong Duplex Outlet Mounting
---------	--

#### Coaxial Cable In-Line Arrestors

RRX4025	Type "N" Connector
RRX4032	Tower Mounting Hardware

### Manuals

6864110R66	CDR500 and CDR700 Service Manual
------------	----------------------------------